

ステータス:	商用リリース	開始日:	2015/12/11
優先度:	通常	期日:	
担当者:	山本 義治	進捗 %:	0%
カテゴリ:	サーバ環境構築	予定工数:	0.00時間
対象バージョン:		作業時間の記録:	0.00時間
説明			
事象			
外部ユーザーがredisに接続してパスワード上書きされた模様 [redis.log] 2015/12/11 01:41:08 [error] 5143#0: *3389 [lua] event_set.lua:134: failed to get redis key: NOAUTH Authentication required., client: 110.132.122.227, server: ad.i-joji.com, request: "GET /event/set?app_id=halooandroid&app_key=8GMqtuiy7Q28a9YM&user_id=db3da703-7c28-49c7-812d-3d40a9e5aa8d&event_type=ad&label=ad_view HTTP/1.1", host: "ad.i-joji.com" http://stackoverflow.com/questions/34115213/redis-raise-error-noauth-authentication-required-but-there-is-no-password-setti			
対策			
・ auth認証 ・ bind制限 bind 127.0.0.1 192.168.1.3 ・ iptablesでIP制限 http://redis.io/topics/security http://antirez.com/news/96 http://cocopoo.com/2015/11/crackredis-io/			

履歴

#1 - 2015/12/17 15:25 - 山本 義治

redis-server再起動

```
[root@ad1 admin]# /etc/init.d/redis stop
Stopping ...
(error) NOAUTH Authentication required.
Waiting for Redis to shutdown ...
Waiting for Redis to shutdown ...
Waiting for Redis to shutdown ...
Waiting for Redis to shutdown ...
[root@ad1 admin]# cat /var/run/redis_6379.pid
1536
[root@ad1 admin]# redis-cli -p 6379 shutdown
(error) NOAUTH Authentication required.
[root@ad1 admin]# service redis-server restart
redis-server: 認識されていないサービスです。
[root@ad1 admin]# kill -9 1536
[root@ad1 admin]# rm /var/run/redis_6379.pid
```

```
[root@ad1 admin]# /etc/init.d/redis start
Starting Redis server...
[root@ad1 admin]# ps ax | grep redis
7589 ?      Ssl  0:00 /usr/local/bin/redis-server *:6379
7594 pts/0  S+   0:00 grep redis
[root@ad1 admin]# redis-cli
127.0.0.1:6379> keys *
(empty list or set)
127.0.0.1:6379> ping
PONG
```

#2 - 2015/12/17 16:38 - 山本 義治

API、Webともredis認証追加

#3 - 2015/12/17 16:38 - 山本 義治

- ステータス を 新規 から 商用リリース に変更

#4 - 2015/12/17 16:38 - 山本 義治

- カテゴリ を サーバ環境構築 にセット

- 担当者を 山本 義治 にセット

#5 - 2015/12/17 16:46 - 山本 義治

datadog設定変更

```
[root@ad1 admin]# vi /etc/dd-agent/conf.d/redisdb.yaml
password: *****
[root@ad1 admin]# /etc/init.d/datadog-agent info
=====
Collector (v 5.6.1)
=====

Status date: 2015-12-17 16:42:44 (12s ago)
Pid: 28217
Platform: Linux-2.6.32-573.7.1.el6.x86_64-x86_64-with-centos-6.7-Final
Python Version: 2.7.10
Logs: <stderr>, /var/log/datadog/collector.log, syslog:/dev/log

Clocks
=====

NTP offset: -0.003 s
System UTC time: 2015-12-17 07:42:57.391871

Paths
=====

conf.d: /etc/dd-agent/conf.d
```

checks.d: /opt/datadog-agent/agent/checks.d

Hostnames

=====

socket-hostname: ad1.i-joji.com

ec2-hostname: ad1.i-joji.com

hostname: ad1.i-joji.com

socket-fqdn: ad1.i-joji.com

Checks

=====

network

- instance #0 [OK]

- Collected 21 metrics, 0 events & 1 service check

ntp

- Collected 0 metrics, 0 events & 1 service check

nginx

- instance #0 [OK]

- Collected 7 metrics, 0 events & 2 service checks

redisdb

- instance #0 [ERROR]: 'NOAUTH Authentication required.'

- Collected 0 metrics, 0 events & 2 service checks

- Dependencies:

- redis: 2.10.3

disk

- instance #0 [OK]

- Collected 24 metrics, 0 events & 1 service check

Emitters

=====

- http_emitter [OK]

=====

Dogstatsd (v 5.6.1)

=====

Status date: 2015-12-17 16:42:55 (2s ago)

Pid: 28215

Platform: Linux-2.6.32-573.7.1.el6.x86_64-x86_64-with-centos-6.7-Final

Python Version: 2.7.10

Logs: <stderr>, /var/log/datadog/dogstatsd.log, syslog:/dev/log

Flush count: 292913
Packet Count: 0
Packets per second: 0.0
Metric count: 1
Event count: 0
Service check count: 0

=====
Forwarder (v 5.6.1)
=====

Status date: 2015-12-17 16:42:57 (1s ago)
Pid: 28216
Platform: Linux-2.6.32-573.7.1.el6.x86_64-x86_64-with-centos-6.7-Final
Python Version: 2.7.10
Logs: <stderr>, /var/log/datadog/forwarder.log, syslog:/dev/log

Queue Size: 0 bytes
Queue Length: 0
Flush Count: 942205
Transactions received: 445643
Transactions flushed: 445643

[root@ad1 admin]# /etc/init.d/datadog-agent restart
Stopping Datadog Agent (using killproc on supervisord): [OK]
Starting Datadog Agent (using supervisord): [OK]
[root@ad1 admin]# /etc/init.d/datadog-agent info

=====
Collector (v 5.6.1)
=====

Status date: 2015-12-17 16:43:15 (2s ago)
Pid: 9439
Platform: Linux-2.6.32-573.7.1.el6.x86_64-x86_64-with-centos-6.7-Final
Python Version: 2.7.10
Logs: <stderr>, /var/log/datadog/collector.log, syslog:/dev/log

Clocks
=====

NTP offset: -0.0003 s
System UTC time: 2015-12-17 07:43:17.371947

Paths
=====

conf.d: /etc/dd-agent/conf.d
checks.d: /opt/datadog-agent/agent/checks.d

Hostnames
=====

socket-hostname: ad1.i-joji.com
hostname: ad1.i-joji.com
socket-fqdn: ad1.i-joji.com

Checks

=====

network

- instance #0 [OK]
- Collected 0 metrics, 0 events & 1 service check

ntp

- instance #0 [OK]
- Collected 1 metric, 0 events & 2 service checks

nginx

- instance #0 [OK]
- Collected 4 metrics, 0 events & 2 service checks

redisdb

- instance #0 [OK]
- Collected 29 metrics, 0 events & 2 service checks

disk

- instance #0 [OK]
- Collected 24 metrics, 0 events & 1 service check

Emitters

=====

- http_emitter [OK]

=====

Dogstatsd (v 5.6.1)

=====

Status date: 2015-12-17 16:43:09 (8s ago)

Pid: 9437

Platform: Linux-2.6.32-573.7.1.el6.x86_64-x86_64-with-centos-6.7-Final

Python Version: 2.7.10

Logs: <stderr>, /var/log/datadog/dogstatsd.log, syslog:/dev/log

Flush count: 0

Packet Count: 0

Packets per second: 0

Metric count: 0

Event count: 0

Service check count: 0

=====

Forwarder (v 5.6.1)

=====

Status date: 2015-12-17 16:43:19 (0s ago)

Pid: 9438

Platform: Linux-2.6.32-573.7.1.el6.x86_64-x86_64-with-centos-6.7-Final

Python Version: 2.7.10

Logs: <stderr>, /var/log/datadog/forwarder.log, syslog:/dev/log

Queue Size: 0 bytes

Queue Length: 0

Flush Count: 3

Transactions received: 1

Transactions flushed: 1